


**Rough-In Plumbing Measurements**



## SPECIFICATIONS:

### GENERAL SPECIFICATIONS:

Tub Size	60" x 41 1/2" x 23 3/4"
	152 cm x 105 cm x 60 cm
Bathing Well	36" long
	22 1/2" wide
	22" interior depth
Maximum Water Depth	16 1/2"
Shipping Weight	163 lbs. / 74 kg
Tub Weight Filled	587 lbs. / 266 kg
Tub Only Weight	112 lbs. / 51 kg
Gallons to Overflow	57 gal. / 216 L
Gallons to Operate	44 gal. / 167 L

### ELECTRICAL SPECIFICATIONS:

Pump	.80 HP; 5.5 AMP; 110V
Requirement	15 AMP; 110V, separate circuit required protected w/ Class A GFCI

### STANDARD EQUIPMENT:

- 6 Hydrotherapy Jets including:**
- 2 Spinning Back Jets
  - 4 Directional Jets
- Aquatic Quality Features:**
- .80 HP Run-Dry Pump
  - Bath-Side On/Off Air Button
  - "Quiet Pad" Anti-Vibration Pump Mount for Quiet Pump Operation
  - Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
  - 2 Arm Rests
  - Color Matched Trim and Jets (Select Colors)
  - Durable, Easy to Clean, Lucite® Cast Acrylic Surface
  - Available in 8 Standard No-Charge Colors
- UL and IAPMO Listed, Factory Tested**  
**Limited 10 Year Warranty**

### OPTIONAL EQUIPMENT:

- Comfort Pillow--Oval or Rectangle
- Lift & Turn Waste and Overflow
  - Chrome, Polished Brass, Gold, Satin Nickel, Polished Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
  - Chrome, Polished Brass, Gold, Satin Nickel, Polished Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Optional Pump Location

*All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.*

**Fax-On-Demand Document # 1284**

